



- ✓ Auto rango
- ✓ Gran display dual con retroiluminación
- ✓ Conexión a PC con cable USB
- ✓ Estuche rígido de transporte
- ✓ Frecuencia de medición de hasta 100kHz
- ✓ Prueba PASS-FAIL (test rápido de PASA-NO PASA)
- ✓ Terminales de conexión tipo cocodrilo, zócalo de inserción y pinza tipo tweezer incluidos
- ✓ Rango de medición de inductancia de 20uH hasta 2000H
- ✓ Rango de medición de capacitancia de 200pF hasta 20mF
- ✓ Rango de medición de resistencia de 200hm hasta 20MOhm
- ✓ Medición de parámetros: L/C/R/DCR/Q/D/θ/ESR
- ✓ Software Incluido

Specification	Range	Best Accuracy
<b>Model UT612</b>		
Inductance (H)	20uH~2000H	±(0.5%+5)
Capacitance (F)	200pF~20mF	±(0.5%+5)
Resistance (Ω)	20Ω~200MΩ	±(0.3%+5)
Test Frequency (Hz)	100Hz/120Hz/1KHz/10KHz/100KHz	√
Operational Voltage	0.6Vrms	√
Test Parameters	L/C/R/DCR/Q/D/θ/ESR	√
<b>Features</b>		
Display Count		20000
D/Q Display Count		2000
D/Q Resolution	0.001	√
Auto Range		√
Real-Time Display Test Frequency		√
Measurement Mode	Series/Parallel	√
Auto Power Off		√
Low Battery Indication	≤6.8V	√
Data Hold		√
Relative Mode		√

USB Interface		√
USB Interface/PC Data Records		60000
LCD Backlight		√
Analogue Bar Graph		26
Deviation Ratio Measurement		√
Comparsion Function		√
Calibration Function		√
Output Impedance	120Ω	√
Auto LCR Smart Check and Measurement		√
<b>General Characteristic</b>		
Power	9V Battery (6F22) or USB	
LCD Size	40 X 63mm	
Product Colour	Red and Grey	
Product Net Weight	374g	
Product Size	96 X 193 X 47mm	
Standard Accessories	Battery,SMD Test Clamp,USB Interface Cable,Multi-Purpose Socket,PC Software CD	
Standard Individual Packing	Gift Box, English Manual	
Standard Quantity Per Carton	24 PCs	
Standard Carton Measurement	610mm X 450mm X 355mm (0.097 CBM Per Standard Carton)	
Standard Carton Cross Weight	22.3Kg	
<b>Optional Accessories*</b>		
USB Power Adapter		