

## PM 8229 5 in 1

4000 Counts Multi-Functions Digital Multimeter

DMM TEMP RH dB LUX

### SPECIFICATIONS

	RANGE	ACCURACY
DC Voltage	400mV/4V/40V/400V/1000V	±(0.7%+2)
AC Voltage	400mV/4V/40V/400V/750V	±(0.8%+3)
DC Current	400µA/4000uA/40mA/400mA	±(1.2%+3)
	4A/10A	±(2.0%+10)
AC Current	400µA/4000uA/40mA/400mA	±(1.5%+3)
	4A/10A	±(3.0%+10)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(1.2%+5)
Capacitance	40nF/400nF/4µF/40µF/100µF	±(3.0%+3)
Frequency	10Hz/100Hz/1kHz/10kHz/100kHz	±(2.0%+5)
Duty cycle	1%~99%	±(3.0%+2)
Temperature(°C/°F)	-20°C~1000°C	±(2.0%+2)
	-4°F~1832°F	±(2.0%+2)
Environment(°C/°F)	0°C~40°C	±2°C
	32°F~104°F	±4°F
Relative Humidity	30%~95%	±5.0%
Sound Level	35dB~100dB	±3.5%
Luminosity	4000Lux/40000Lux	±5.0%

### FEATURE

Display	4000 Counts
Auto and manual range	✓
Relative Measurement	✓
Data hold	✓
Diode test	✓
Continuity	✓
Back light	✓

### GENERAL

Power supply	4x1.5V AA batteries
Weight	Approx. 580g
Size	204mm x 93mm x 57mm
Safety Rating	EN61010-1,-2-030,EN61010-2-033, EN61326-1 , CAT.III 1000V

