

BM822, BM823

400A AC & AC/DC MINI-DIGITAL
CLAMPMETER



- 3 1/2 digits LCD display, max. reading 1999
- SMT application
- Rotary switch for one hand operation
- Capacitance, frequency measurement
- Data hold, auto-power off
- Over load protection
- Safety: IEC1010 600V Cat.II

Technical specifications

DCV: 400m/4/40/400/600V, $\pm 0.8\%$

ACV: 4/40/400/600V, $\pm 1.2\%$

DCA: 40/400A, $\pm 2.0\%$ (M823 only)

ACA: 4/40/400A, $\pm 1.9\%$ (50~100Hz)

OHM: 400/4k/40k/400k/4M/40M Ω , $\pm 1.0\%$

CAP: 40n/400n/4 μ /40 μ /100 μ F, $\pm 3.0\%$

FREQ: 40/400/4k/40k/400k/4M/20MHz, $\pm 0.5\%$

Continuity buzzer: <50

Diode test: 1.5V/0.5mA

Clamp size: ϕ 30mm (max.)

Dimensions: 162x65x27mm

Weight: approx. 140g (incl. battery)

Battery: 1.5Vx2, AAA **size**

Accessories: carrying **bag**

REF: 030822X0000

CE (EMC), UL, CE (LVD)